

CITY OF DELAND
120 S. FLORIDA AVENUE 1ST FLOOR BUILDING DIVISION
386-626-7009 PHONE / 386-626-7135 FAX
Commercial Roof Slope Application

Deck Type	
Underlayment	Weight=
Roof Slope:	Layers=
_____	() ASTM D 226 Type 1 Or () ASTM D 4869 Type 1
Insulation	N/A
Fastener Type	N/A
Cap Sheet	N/A
Roof Covering	Manufacturer: Asphalt Shingles Must Comply with: () ASTM D 225 or () ASTM D3462
Fasteners	Attachment Shall Comply With: () ASTM D 3161 or () M-DC PA 107-35
Drip Edge	

Number of Squares: _____

Mean Height: _____

Contractor: _____

Owner: _____

Job Site: _____

** Reroof permits require a minimum of two inspections.

RUND= Roof Underlayment and flashing

ROOF= Final Installation

Fasteners to be corrosion resistant conforming to 1507.2.6 FBC, ASTM F 1667 and ASTM A 641, Class 1 and 1507.2.7.

Underlayment to comply with 1507.2.3 and FBC (testing per ASTM D 226 Type 1 or ASTM D 4869, Type 1) and APPLICATION to 1507.2.8 FBC.

Asphalt Shingles to comply with 1507.2 FBC and ASTM D 225 or ASTM D 3462 and 1507.2.5 FBC ATTACHMENT shall conform to ASTM D 3161 (modified to 110 mph) or M-DC-107-95.

Flashing to comply with 1507.2.9 FBC / **Drip Edge** to comply with 1507.2.9.3 / FBC = Florida Building Code 2004.

*** Note: A product wrapper containing the product information needs to be placed with the permit placard for both RUND and ROOF inspections.